

PASSIVE DESIGN APPROACH IN ENHANCING NATURAL VENTILATION
PERFORMANCE OF TWO STOREYS RESIDENTIAL BUILDINGS IN TROPICAL
CLIMATE

IZUDINSHAH BIN ABD. WAHAB

A thesis submitted in
fulfillment of the requirement for the award of the
Doctor of Philosophy.



Faculty of Civil and Environmental Engineering
University Tun Hussein Onn Malaysia

JANUARY, 2018

To Allah the Almighty,

For my beloved mother and father,
my wife and children,



PTTA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

ACKNOWLEDGEMENT

I believe that I would not have been able to complete this PhD journey without the support and cooperation of countless people over the years. Thank you to Universiti Tun Hussein Onn Malaysia and Ministry of Higher Education for the financial support of this research. My special thanks also goes to Prof. Dr. Ahmad Tarmizi Abd. Karim, former Dean of Faculty of Civil and Environmental Engineering who allowed and encouraged me to pursue this PhD journey,

Hereby, I would like to express my sincere gratitude to my supervisor, Assoc. Prof. Dr. Lokman Hakim bin Ismail and co-supervisor, Assoc. Prof. Dr. Abd. Halid bin Abdullah, who is currently the Dean of Faculty of Civil and Environmental Engineering for their excellent guidance, patience, and providing me motivation to complete the research. My gratitude also goes to Dr. Azeanita binti Suratkon, my former Head of Architecture and Design Engineering Department for patiently allowing me juggling my task under the department and my commitment to complete this research.

I would also like to appreciate my research team members, for their helpful assistance throughout the research work. Special thanks also goes to Mr. Osman Abd. Rahman, the technician for Building Services Laboratory for assistance with the research equipment.

Last but not least, my foremost gratitude is to my wife, Anizah Masini for being there persistently encouraging me as always, and to my children, Muhammad Irfan, Muhammad Izz Israq and Irdina for their patience and understanding. Similar gratitude also goes to my parents, Mr. Abd. Wahab Hashim and Mrs. Hafsa Jaafar for their endless love and prayers. To my family and parents, I thank you for your fullest support.

ABSTRACT

Air movement is one of the main factors contributing to thermal comfort. In achieving the comfort while maintaining low energy consumption, natural ventilation is the best source of air movement to be relied on. However, inconsistency of surrounding air movement in urban areas may not provide sufficient air flow for building in the area. Based on previous research, there are building design elements that show potential in contributing good indoor natural ventilation within the surrounding. Throughout case studies, this research identifies the elements which further specified as natural ventilation attributes. Result shows, wind catcher attribute turn to be the most significant followed by wide openings and indoor layout. Whereas louvered openings show possibilities in enhancing the incoming air velocity by-passing them. Using a full-scale single unit double storey house prototype, this research applies the potential attributes to the design before being analyzed on the building indoor air movement effect. The ratio of the overall indoor air movement upon outdoor air movement at particular hours was used to indicate the space indoor natural ventilation performance for the building. The result shows significant high incoming air velocity through the aerofoil louvered wind catcher applied as the high opening for the building atrium. The high air velocity was maintained at the upper area inside the atrium before rapidly reduced along its way down. The low positioning of the neutral pressure plane (NPP) level in the building kept the process flows. Wide openings provided at upper level, even are not directly attached to the atrium may cause air short cut flowing out along the way down. However, wide openings at lower level, significantly contribute good air flow despite slower crossing ventilation flowing at the level. In a situation when the surrounding air is almost stagnant, the design was found still capable to keep the air movement flow via stack effect ventilation. The research also found that while it is important for the building to enhance the incoming air flow, it is also important to provide a properly planned layout design to manage the indoor air flow.

ABSTRAK

Pergerakan udara adalah salah satu faktor utama keberhasilan termal. Dalam usaha mencapai keberhasilan sambil memastikan penggunaan tenaga kekal rendah, pengudaraan semulajadi merupakan sandaran yang baik. Namun begitu, ketidakpastian pergerakan udara di persekitaran kawasan bandar mungkin tidak mampu membekalkan aliran angin yang mencukupi untuk bangunan di kawasan berkenaan. Berdasarkan kajian terdahulu, didapati terdapat beberapa elemen bangunan yang menunjukkan potensi untuk menyumbang pengudaraan dalaman yang baik dalam persekitaran begitu. Menerusi kajian kes, penyelidikan ini telah mengenalpasti elemen-elemen tersebut. Ianya dikenali sebagai atribut pengudaraan semulajadi menerusi spesifikasi yang diberikan untuk setiap satunya. Hasil penyelidikan mendapati perangkap angin merupakan atribut terbaik yang menyumbang kepada pengudaraan semulajadi dalaman. Selain itu, bukaan luas dan susunatur ruang dalaman turut menyumbang kepada pengudaraan itu. Sementara bukaan dengan sisir angin didapati dapat mempertingkatkan kelajuan angin yang melaluinya memasuki bangunan. Dengan membangunkan sebuah prototaip rumah berskala sebenar, penyelidikan ini mengaplikasikan atribut-atribut tersebut untuk seterusnya dinilai kesannya terhadap pengudaraan semulajadi ruangan dalamannya. Perbandingan pergerakan udara dalaman terhadap pergerakan udara luaran bagi sesuatu ruang digunakan sebagai penentuan prestasi pengudaraan semulajadi ruangan tersebut. Hasil penyelidikan mendapati terdapat pergerakan udara yang tinggi memasuki bangunan menerusi perangkap udara bersisir aerofoil yang diaplikasi sebagai bukaan tinggi di ruang atrium bangunan. Ianya kekal tinggi di bahagian atas atrium tersebut sebelum turun mendadak apabila bergerak ke bawah. Kesan kedudukan aras tekanan neutral (NPP) yang rendah pada bangunan memberi kesan proses ini berterusan. Walaupun terasing dari ruang atrium, bukaan luas yang diaplikasi berkemungkinan memberi kesan pengudaraan pintas terutamanya di ruang dalaman tingkat atas. Sementara itu di ruang bawah, bukaan luas membenarkan pergerakan udara yang baik ke dalam bangunan walaupun pengudaraan lintang di persekitarannya adalah perlahan. Namun begitu dalam keadaan tiada angin lintang, rekabentuk ini masih berupaya mengekalkan pergerakan angin ruang dalaman menerusi kesan pengudaraan tindanan (*stack*).

Penyelidikan ini mendapati, selain memberi tumpuan untuk membawa pergerakan angin, merancang susunatur ruang dalaman juga adalah penting bagi memastikan pergerakan angin dalamannya adalah teratur dan berkesan.



PTTA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

TABLE OF CONTENTS

TITLE	i
STUDENT DECLARATION	v
DEDICATION	vi
ACKNOWLEDGEMENTS	vii
ABSTRACT	viii
ABSTRAK	ix
TABLE OF CONTENTS	xi
LIST OF TABLES	vii
CHAPTER 1 INTRODUCTION	1
1.1 Overview	1
1.2 Background of study	2
1.3 Problem statement	4
1.4 Research questions	7
1.5 Hypothesis	8
1.6 Aim and research objectives	9
1.7 Significance of research	10
1.8 Scope of study	11
1.9 Research methodology	12
1.10 Thesis outline	13
1.11 Conclusion	14
CHAPTER 2 AIR MOVEMENT FACTORS FOR THERMAL COMFORT IN BUILDING	15
2.1 Introduction	15
2.2 Human comfort	17
2.2.1 Visual comfort	17
2.2.2 Acoustic comfort	18

2.2.3	Thermal comfort	18
2.3	Indoor air quality	20
2.4	Building ventilation	21
2.4.1	Cross ventilation.	23
2.4.2	Stack effect ventilation	24
2.4.3	Natural pressure plane effect on stack ventilation	26
2.5	Building ventilation opening	28
2.6	Window design	29
2.7	Louvers window design	31
2.8	Louvers design	32
2.9	Air jet	33
2.10	Summary of findings	34
2.11	Conclusion	35

CHAPTER 3 ARCHITECTURAL APPROACH FOR NATURAL VENTILATION STRATEGIES

3.1	Introduction	37
3.2	Architectural design	39
3.2.1	Architectural design development flow	39
3.2.2	Legal aspect on technical matters in architectural design	40
3.2.2	Construction process and project management	41
3.2.3	Building engineering in architectural design	41
3.3	Factors effecting natural ventilation on building	42
3.4	Building design attributes identification	52
3.5	Ventilation strategies in vernacular architecture	61
3.5.1	Vernacular building layout and orientation	61
3.5.2	Vernacular building form	62
3.6	Ventilation strategies in contemporary architecture	65
3.6.1	Wind scoops or wind catcher element	65
3.6.2	Open plan concept	67

3.6.3	Roof design	69
3.7	Summary of findings	70
3.8	Conclusion	70
CHAPTER 4	RESEARCH METHODOLOGY	72
4.1	Introduction	72
4.2	Research approach	72
4.2.1	Qualitative method	73
	4.2.1.1 Case study method	74
	4.2.1.2 Design process method	75
4.2.2	Quantitative method	75
	4.2.2.1 On-field data measurement	76
	4.2.2.2 Indoor natural ventilation performance	78
	4.2.2.3 Wind tunnel simulation	78
4.3	Research method adopted	80
4.3.1	Literature review	81
4.3.2	Case Studies	82
	4.3.2.1 Preparation of the field study on case studies	88
	4.3.2.2 Data collection	91
	4.3.2.3 Data obtained	92
	4.3.2.4 Data analysis	92
4.3.3	Design process	93
	4.3.3.1 Identifying the site	93
	4.3.3.2 Construction legislation matters	94
	4.3.3.3 Micro-climate of meteorological data of site	94
	4.3.3.4 Design development	94
	4.3.3.5 Wind tunnel experimental work	95
4.3.4	Full scale prototype design development on site	96
4.4	Prototype analysis	96
4.4.1	On-field data collection of the prototype	96



4.5	Research overview	98
4.6	Conclusion	100
CHAPTER 5	NATURAL VENTILATION ATTRIBUTES IDENTIFICATION	101
5.1	Introduction	101
5.2	Objective of case studies	101
5.3	Case studies of vernacular house	102
5.3.1	Sri Banai house, Alor Setar, Kedah	102
5.3.2	Tok Su house, Alor Setar, Kedah	106
5.3.3	Kalimantan Tengah traditional house	109
5.3.4	Batak Toba house, the house of North Sumatera	112
5.4	Case studies on contemporary houses with vernacular elements	116
5.4.1	Sri Merlong house, Rengit, Johor	116
5.4.2	Sri Penggaram house, Batu Pahat, Johor	120
5.5	Case studies on contemporary house with natural ventilation design approach	123
5.5.1	Sekeping Seapark, Petaling Jaya	123
5.5.2	Skudai Box, Johor Bahru	129
5.6	Data analysis	132
5.6.1	Indoor natural ventilation performance	132
5.5.2	Significant natural ventilation attributes identification	134
5.5.3	Natural ventilation attributes contribution analysis	144
5.7	Summary finding of objective 1	147
5.8	Conclusion	148
CHAPTER 6	DESIGNING THE ATTRIBUTES COMBINATION ON A BUILDING	149
6.1	Introduction	149
6.2	Identifying the site	149
6.3	Construction legislation matters	150

6.4	Micro climate studies	152
6.4.1	Meteorological district data	153
6.4.2	Site studies on weather data	155
6.4.3	Conclusion on weather data	162
6.5	Design process	163
6.5.1	Setting the building footprint	163
6.5.2	Space arrangement	164
6.5.3	Natural ventilation attributes application	165
6.5.4	Wind tunnel simulation of natural ventilation effect on the building form	171
6.6	Design development	178
6.7	Full scale prototype development on site	178
6.7.1	Building plan approval from local authorities and technical departments	178
6.7.2	Construction process	179
6.8	Summary finding of objective 2	180
6.9	Conclusion	182
CHAPTER 7 INDOOR NATURAL VENTILATION PERFORMANCE ENHANCEMENT		183
7.1	Introduction	183
7.2	Data collection	183
7.2.1	Outdoor wind velocity and air temperature	185
7.2.2	Comparison of outdoor wind velocity and indoor air movement	187
7.2.3	Comparison of outdoor and indoor air temperature	192
7.3	Indoor natural ventilation performance	196
7.3.1	Previous finding comparison	198
7.3.2	Case studies comparison	199
7.4	Natural ventilation attributes application analysis	202
7.4.1	Aerofoil louvered wind catcher atrium	202
7.4.2	Opening design	205
7.4.3	Centralized atrium indoor layout	209

7.4.4	Lowering the neutral pressure plane (NPP) level	210
7.5	Summary findings of objective 3	212
7.6	Conclusion	213
CHAPTER 8	CONCLUSION AND RECOMMENDATIONS	214
8.1	Introduction	214
8.2	Summary of research development.	214
8.3	Hypotheses review	216
8.4	Contribution to knowledge	217
8.5	Limitation of research	219
8.6	Recommendation for future research	220
8.7	Conclusion	221
	REFERENCES	
	APPENDICES	



LIST OF TABLES

2.1	Temperature, relative humidity and air velocity comfort range comparison	20
4.1	Building selected under the category of case studies	74
4.2	Sample of Matrix Comparison Table	76
4.3	Research methodology phases	81
4.4	Determination of field study period	89
4.5	Monthly average wind speed of Batu Pahat	97
4.6	Research methodology overview for Phase 1	98
4.7	Research methodology overview for Phase 2	99
4.8	Research methodology overview for Phase 3	99
5.1	Mean outdoor air velocity of case studies	133
5.2	Indoor Natural Ventilation performance on determined observed spaces	133
5.3	Analysis of natural ventilation building elements presence in determined case study spaces	145
5.4	Ventilation attributes significance on good indoor natural ventilation performance	147
6.1	Meteorological data of wind velocity in Batu Pahat	153
6.2	Matrix space interrelation	164
6.3	Matrix of attribute relation with other attributes	165
6.4	Matrix comparison of natural ventilation attributes and building spaces	166
7.1	The outdoor mean data of wind velocity and air temperature	187
7.2	Indoor natural ventilation performance of 7.00am to 6.00pm period	197
7.3	Indoor natural ventilation performance of 7.00pm to 6.00am period	198
7.4	Indoor natural ventilation performance of living hall comparison	200
7.5	Indoor natural ventilation performance of family hall comparison	201

7.6	Indoor natural ventilation performance of bedrooms comparison	201
7.7	Comparison of indoor and outdoor reading indicating buoyancy effect	204



PTTA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

LIST OF FIGURES

1.1	Outdoor against indoor daily temperature of concrete house	5
1.2	Design requirements of cross ventilation and stack effect ventilation	6
1.3	The thesis structure	14
2.1	Location of tropical climates	16
2.2	Thermal comfort, visual comfort and acoustic comfort:	17
2.3	Diagram showing type of natural ventilation.	22
2.4	Cross ventilation diagram.	24
2.5	Stack ventilation diagram process in building.	25
2.6	Schematic diagram of stack ventilation in a workshop.	27
2.7	Purpose provided openings and adventitious openings.	29
2.8	Overall design impact on ventilation.	30
2.9	The average of air temperature without stack ventilation	31
2.10	The average of air temperature with stack ventilation	31
2.11	Ordinary shape of louvers	32
2.12	Vector flow for 45° angle louvers pointing down	32
2.13	Louvers window application on contemporary building design	33
2.14	Typical air jet distribution condition in room showing trajectory and gravity impact	34
3.1	Proposed adaptive comfort standard (ACS) for ASHRAE Standard 55, applicable for naturally ventilated buildings.	38
3.2	Knowledge exploration in design process	40
3.3	Building orientation towards the cardinal direction	43
3.4	Overheating temperature-indices for the 4 glazing system at various wall orientations (GL1-GL4) based on mediterranean region surrounding simulation	44
3.5	Bioclimatic tower	45

3.6	Building form showing air supply strategy (left) and air exhaust strategy	46
3.7	Air movement of wind catcher study	47
3.8	Comparison study of side lit atrium (left) and top lit atrium (right) effect on indoor thermal condition	49
3.9	Large vortex due to higher angle attack	51
3.10	Computation Fluid Dynamic simulation showing velocity counters for aerofoil louvers model (a)25° (b)35° (c)45°	51
3.11	Building and landscape elements roles in directing the wind flow	54
3.12	Louvers windows application in building	55
3.13	Central level of high window opening at 2/3 of the floor to ceiling height	56
3.14	The example of Open Plan concept determined	57
3.15	The examples of Open Plan concept interior look	57
3.16	Low opening maximum height determination	58
3.17	Wind flow within 45 degree angle of direction to benefit the facing opening	59
3.18	Sample of Wind Rose Diagram to represent the surrounding pattern of wind flow	59
3.19	Determination of High Ceiling and Raised Floor	60
3.20	Building orientation study on a traditional house in Quang Nam	62
3.21	Air movement velocity of indoor spaces (No. 2 - 7) comparison with overall outdoor air movement velocity	63
3.22	Indoor cross ventilation at habitable level in Malay vernacular house	64
3.23	High ceiling for better indoor air movement (a) House in Tien Giang, Vietnam (b) House in Hanoi, Vietnam	64
3.24	Detail roof joint with opening gap allowing ventilation flow	64
3.25	Cross Sectional view and Isometric sketches of Roof-Roof House showing the cross ventilation approaching the pool side	66
3.26	The shaded area by the pool side of Roof-Roof House with wide openings to allow the crossing ventilation flow through the interior spaces	66

3.27	The thin shaped building form with wide openings facing the direction of wind flow in Razorblade Pairs semi- detached	67
3.28	Chempenai House	68
3.29	Sekeping Serendah by Seksan Design	69
4.1	Research method flow	73
4.2	(a) Anemometer, (b) E-Sampler	77
4.3	Laser distance meter	77
4.4	Wind Tunnel at Faculty of Mechanical and Manufacturing Engineering, Universiti Tun Hussein Onn Malaysia	79
4.5	Wind Tunnel at Faculty of Civil and Environmental Engineering, Universiti Tun Hussein Onn Malaysia	80
4.6	Seri Banai House, Alor Setar, Kedah	83
4.7	Tok Su House, Alor Setar, Kedah	83
4.8	Kalimantan Tengah House, Indonesia	84
4.9	Batak Toba House of North Sumatera	84
4.10	Sri Merlong House, Rengit, Johor	85
4.11	Sri Penggaram House of Batu Pahat, Johor	86
4.12	Sekeping Seapark, Petaling Jaya, Selangor	87
4.13	Skudai Box, Johor Bahru	88
4.14	Process flow of Site Identification	93
5.1	Sri Banai house, Alor Setar, Kedah	102
5.2	Sri Banai house floor plan	103
5.3	Sri Banai house sectional view 1	103
5.4	Sri Banai house sectional view 2	104
5.5	Sri Banai house air velocity comparison Point 1 to Point 6	104
5.6	Sri Banai house air velocity comparison Point 7 to Point 12	104
5.7	Sri Banai house air velocity comparison Point 13 to Point 14	105
5.8	Sri Banai house air velocity comparison Point 15 to Point 20	105
5.9	Tok Su house, Alor Setar, Kedah	106
5.10	Tok Su house floor plan	107
5.11	Tok Su house sectional view Y-Y	107
5.12	Tok Su house air velocity comparison Point 1 to Point 5	108
5.13	Tok Su house air velocity comparison Point 6 to Point 8	108

5.14	Tok Su house air velocity comparison Point 9 to Point 11.	108
5.15	Tok Su house air velocity comparison Point 12 to Point 15	109
5.16	Kalimantan Tengah traditional house.	109
5.17	Kalimantan Tengah house floor plan.	110
5.18	Kalimantan Tengah house sectional view	110
5.19	Kalimantan Tengah house air velocity comparison Point 1 to Point 6	111
5.20	Kalimantan Tengah house air velocity comparison Point 7 to Point 15	111
5.21	Kalimantan Tengah house air velocity comparison Point 16 to Point 21	112
5.22	Kalimantan Tengah house air velocity comparison Point 10 to Point 12	112
5.23	Batak Toba house, the house of North Sumatera.	113
5.24	Batak Toba house floor plan.	113
5.25	Batak Toba house sectional view	114
5.26	Batak Toba house air velocity comparison Point 1 to Point 3	114
5.27	Batak Toba house air velocity comparison Point 4 to Point 6	115
5.28	Batak Toba house air velocity comparison Point 7 to Point 9	115
5.29	Batak Toba house air velocity comparison Point 10 to Point 12	116
5.30	Batak Toba house air velocity comparison Point 13 to Point 14	116
5.31	Sri Merlong house of Rengit, Johor	117
5.32	Sri Merlong house floor plan	117
5.33	Sri Merlong house sectional view	118
5.34	Sri Merlong house air velocity comparison Point 1 to Point 6 at daytime	118
5.35	Sri Merlong house air velocity comparison Point 7 to Point 9 at daytime	119
5.36	Sri Merlong house air velocity comparison Point 1 to Point 6 at night	119
5.37	Sri Merlong house air velocity comparison Point 7 to Point 9 at night	120
5.38	Sri Pengaram house of Batu Pahat, Johor	120

5.39	Sri Penggaram house sectional view.	121
5.40	Sri Penggaram house floor plan.	121
5.41	Sri Penggaram house air velocity comparison Point 1 to Point 4	122
5.42	Sri Penggaram house air velocity comparison Point 5 to Point 8	122
5.43	Sekeping Seapark of Petaling Jaya, Selangor	124
5.44	Sekeping Seapark sectional view Y-Y	124
5.45	Sekeping Seapark floor plan	125
5.46	Sekeping Seapark sectional view X-X	125
5.47	Sekeping Seapark air velocity comparison Pont 1 to Point 6 at daytime	126
5.48	Sekeping Seapark air velocity comparison Pont 7 to Point 10 at daytime	127
5.49	Sekeping Seapark air velocity comparison Pont 11 to Point 14 at daytime	127
5.50	Sekeping Seapark air velocity comparison Pont 1 to Point 6 at night	128
5.51	Sekeping Seapark air velocity comparison Pont 7 to Point 10 at night	128
5.52	Sekeping Seapark air velocity comparison Pont 11 to Point 14 at night	129
5.53	Skudai Box of Skudai, Johor Bahru	129
5.54	Skudai Box floor plan	130
5.55	Skudai Box sectional view	131
5.56	Skudai Box air velocity comparison Point 1 to Point 4	131
5.57	Skudai Box air velocity comparison Point 5 to Point 8	131
5.58	Sri Merlong floor plan showing the indoor natural ventilation high performance areas layout and the building elements.	135
5.59	Sri Banai floor plan showing the indoor natural ventilation high performance areas layout and the building elements.	136
5.60	Tok Su house floor plan showing the indoor natural ventilation high performance areas layout and the building elements.	138
5.61	Batak Toba house floor plan showing the indoor natural ventilation high performance areas layout and the building elements	139

5.62	Kalimantan long house floor plan showing the indoor natural ventilation high performance areas layout and the building elements	141
5.63	Sekeping Seapark house floor plan showing the indoor natural ventilation high performance areas layout and the building element	142
5.64	Skudai Box floor plan showing the indoor natural ventilation high performance areas layout and the building elements	143
6.1	Proposed site location and surrounding	150
6.2	Surrounding view; (a) Terrace houses at front, (b),(c),(d) Single unit houses at sides	151
6.3	Building setback lines indicating the building footprint on site	152
6.4	Batu Pahat monthly average wind velocity	154
6.5	Batu Pahat monthly mean temperature	154
6.6	Batu Pahat monthly relative humidity	154
6.7	Micro climate studies on site	155
6.8	Data measurement on site before the building construction	156
6.9	Data on wind velocity on site	157
6.10	Data on air temperature at site	158
6.11	Data on relative humidity at site	159
6.12	Wind velocity and direction on site	160
6.13	Building footprint	163
6.14	Bubble diagram of space arrangement.	165
6.15	Conceptual design of the central atrium.	167
6.16	Wide opening; (a) Positioning of the openings, (b) Detail of opening panel	168
6.17	Ground floor plan.	169
6.18	First floor plan.	169
6.19	Neutral pressure plane level effect on air flow.	170
6.20	Developing the scaled model and wind tunnel simulation.	171
6.21	Roof model analysis.	172
6.22	Graph of wind velocity on simulated roof design effect.	173
6.23	Air velocity measurement points of the louver blades simulation	175
6.24	Air velocity comparison of aerofoil and flat louver blades.	176

6.25	Wind flow and velocity simulation on angle attack of louver blades.	177
6.26	Louvers angle effect on wind velocity.	177
6.27	The finalized design of the building as the full scale prototype.	179
6.28	Construction progress.	180
6.29	Design process work scope and flow	181
7.1	Ground floor plan of <i>Kebun Angin</i> showing the points data measured.	184
7.2	First floor plan of <i>Kebun Angin</i> showing the points data measured.	184
7.3	Cross section view of <i>Kebun Angin</i> showing the points data measured.	185
7.4	Data collection using portable anemometer at various points	186
7.5	Data collection using Indoor Air Quality Data logger for the control data	186
7.6	(a)Outdoor mean wind velocity; (b)Outdoor mean air temperature.	187
7.7	<i>Kebun Angin</i> house air velocity comparison Point 1 to Point 5 from 7.00am to 6.00pm.	188
7.8	<i>Kebun Angin</i> house air velocity comparison Point 6 to Point 10 from 7.00am to 6.00pm	188
7.9	<i>Kebun Angin</i> house air velocity comparison Point 11 to Point 15 from 7.00am to 6.00pm	189
7.10	<i>Kebun Angin</i> house air velocity comparison Point 16 to Point 19 from 7.00am to 6.00pm	189
7.11	<i>Kebun Angin</i> house air velocity comparison Point 1 to Point 5 from 7.00pm to 6.00am	190
7.12	<i>Kebun Angin</i> house air velocity comparison Point 6 to Point 10 from 7.00pm to 6.00am	191
7.13	<i>Kebun Angin</i> house air velocity comparison Point 11 to Point 15 from 7.00pm to 6.00am	192
7.14	<i>Kebun Angin</i> house air velocity comparison Point 16 to Point 19 from 7.00pm to 6.00am	192

7.15	<i>Kebun Angin</i> house air temperature comparison Point 1 to Point 5 from 7.00am to 6.00pm	193
7.16	<i>Kebun Angin</i> house air temperature comparison Point 6 to Point 10 from 7.00am to 6.00pm	193
7.17	<i>Kebun Angin</i> house air temperature comparison Point 11 to Point 15 from 7.00am to 6.00pm	194
7.18	<i>Kebun Angin</i> house air temperature comparison Point 16 to Point 19 from 7.00am to 6.00pm	194
7.19	<i>Kebun Angin</i> house air temperature comparison Point 1 to Point 5 from 7.00pm to 6.00am	195
7.20	<i>Kebun Angin</i> house air temperature comparison Point 6 to Point 10 from 7.00pm to 6.00am	195
7.21	<i>Kebun Angin</i> house air temperature comparison Point 11 to Point 15 from 7.00pm to 6.00am	196
7.22	<i>Kebun Angin</i> house air temperature comparison Point 16 to Point 19 from 7.00pm to 6.00am	196
7.23	Atrium attributes combination	203
7.24	Indoor natural ventilation performance comparison against opening size percentage	205
7.25	Indoor natural ventilation performance comparison against opening orientation	206
7.26	Indoor natural ventilation performance comparison against opening level	206
7.27	Indoor natural ventilation performance comparison against louvers percentage upon opening size	207
7.28	The roof design acting as the wind catcher for the central atrium upper opening	209
7.29	Effect of cross ventilation on studying area	209
7.30	Air movement velocity in the atrium shaft	211

LIST OF SYMBOLS AND ABBREVIATIONS

p	-	air temperature.
P_9	-	outdoor air temperature.
x	-	Independent variables
A	-	smallest value inlet (sqm)
ACEM	-	Association of Consulting Engineers of Malaysia
ASHRAE	-	American Society of Heating, Refrigerating and Air- Conditioning Engineers
CO_2	-	Carbon Dioxide
CO	-	Carbon Oxide
dB	-	Decibels
F_1	-	area of lower opening (m^2)
F_2	-	area of upper opening (m^2).
g	-	gravitational constant (9.81m/s)
GBI	-	Green Building Index
H	-	total hight between upper an lower openings (m).
h	-	stack height
h_1	-	height of lower opening to the neutral pressure plane (m).
h_2	-	height of neutral pressure plane to upper opening (m).
HVAC	-	Heat, ventilation and air conditioning system
IAQ	-	Indoor air quality
JKR	-	Public Work Department.
K	-	factor that accounts for orifice characteristics (assumed = 0.65)
MPBP	-	Majlis Perbandaran Batu Pahat.

NPP	-	Neutral pressure plane
PAM	-	Pertubuhan Akitek Malaysia
SAJ	-	Syarikat Air Johor
Ti	-	Indoor temperature (°Celcius).
To		Outdoor temperature (°Celcius).
UBBL 1984		Uniform Building By Law (1984)
V	-	Estimated air flow (m ³ /s)
ZPS		Zero pressure spot



PTTA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

REFERENCES

- Abdullah, A. H. (2007). A Study on Thermal Environmental Performance in Atria in the Tropics with Special Reference to Malaysia. PhD Thesis, Herriot Watt University, UK.
- Abdullah, A. H. & Wang, F. (2011). Modelling thermal environmental performance in top-lit Malaysian atrium using computational fluid dynamics (CFD). *International Journal of Integrated Engineering*, 1(2), 27-42.
- Abdullah, A. H. & Wang, F., (2012). Design and low energy ventilation solutions for atria in the tropics. *Sustainable Cities and Society* 2. pp. 8-28. Elsevier Science Ltd.
- Abidin, N. Z. (2010). Investigating the awareness and application of sustainable construction concept by Malaysian developers. *Habitat International*, 34(4), 421-426.
- Abro, R. S. (1994). Recognition of Passive Cooling Techniques. *Renewable Energy*, Vol. 5, Issue 5-8, pp. 1143-1146. Elsevier Science Ltd.
- Ackerman, D., (1990). *A Natural History of the Senses*. Vantage Books, New York.
- Adamu, Z. A. (2013). The feasibility of natural ventilation in healthcare buildings. PhD Thesis, Loughborough University, Leicestershire, UK
- Aflaki, A., Mahyuddin, N. & Baharum, M. R. (2016). The influence of Single Sided Ventilation Towards the Indoor Thermal Performance of High Rise Building; A Field Study. *Energy and Building*, 126, pp. 146-158. Elsevier Science Ltd.

- Aflaki, A., Mahyuddin, N., Mahmoud, Z. A. C., & Baharum, M. R. (2015). A review on natural ventilation applications through building façade components and ventilation openings in tropical climates. *Energy and Buildings*, 101, 153-162.
- Ahmad, M. H. & Ibrahim, M. N. (1999). A Comparative Study on The Performance of Side Lit Atria and Top Lit Atria in Loq Latitude Tropics of Kuala Lumpur, Malaysia. *Jurnal Alam Bina*, Jilid 2, No. 1, pp. 13-16. FAB UTM, Skudai.
- Ahmad, M. H. & Rasdi, M. T. H. M. (2000). Design Principle of Atrium Building for The Tropics. Penerbit UTM, Skudai.
- Ahmed, N. A. & Wongpanyathaworn, K. (2012). Optimizing Louver Location to Improve Indoor Thermal Comfort Based on Natural Ventilation. *Procedia Engineering* Vol. 49, pp. 169 - 178. Elsevier Science Ltd.
- Allard, F. (1998). *Natural Ventilation in Buildings*. James & James, London.
- Allocca, C., Chen, Q. & Glicksman, L. R. (2003). Design Analysis of Single Sided Natural Ventilation. *Energy and Building* 35(8), pp. 785 - 795. Elsevier Science Ltd.
- Al-Tamimi, N. A. M., Fadzil, S. F. S., & Harun, W. M. W. (2011). The effects of orientation, ventilation, and varied WWR on the thermal performance of residential rooms in the tropics. *Journal of Sustainable development*, 4(2), 142.
- Althof, J., Smithart, E., & Sidebottom, J. (2001). The HVAC response to the energy challenge. *ASHRAE journal*, 43(5), 40.
- Al-Tmeemy, S. M. H. M., Abdul-Rahman, H., & Harun, Z. (2011). Future criteria for success of building projects in Malaysia. *International Journal of Project Management*, 29(3), 337-348.
- American Society of Heating, Refrigerating and Air-Conditioning Engineers
ASHRAE Handbook – Fundamentals (Atlanta, GA: ASHRAE) (2009)
- Antarikananda, P., Duvlov, E. & McCartney, K. (2006). Lesson from Traditional Architecture: Design for a Climatic Responsive Contemporary House in Thailand. *Proceeding of the 23rd Conference on Passive and Low Energy Architecture*, 6-8 September 2006, Geneva.

- Anthony, S. (2011). Rooted Modernity: Interview with Ng Seksan. *Journal of LA India*. Retrieved http://www.seksan.com/txt_india.html
- Artmann, N., Manz, H. & Heiselberg, P. (2007). Climatic potential for passive cooling of buildings by nighttime ventilation in Europe. *Applied Energy* 84, pp 187-201.
- Aryan, A., Ehsan, Z., Amin, S. & Masoud, K. (2010). Wind Catcher: Remarkable Example of Iran Sustainable Architecture. *Journal of Sustainable Development*, Vol. 3, No. 2, pp. 90-97.
- Ascione, F., Bianco, N., De Masi, R. F., & Vanoli, G. P. (2013). Rehabilitation of the building envelope of hospitals: Achievable energy savings and microclimatic control on varying the HVAC systems in Mediterranean climates. *Energy and Buildings*, 60, 125-138.
- Atkinson, J., Chartier, Y., Silvia, C. L. P., Jensen, P., Li, Y., & Seto, W. H. (Eds.). (2009). *Natural ventilation for infection control in health-care settings*. World Health Organization, Geneva.
- Awbi, H. B. (1994). Design Considerations for Naturally Ventilated Building. *Renewable Energy Vol. 5 Part II*, pp. 1081-1090. Elsevier Science Ltd.
- Awbi, H. B. (2007). *Ventilation Systems Design and Performance*. Taylor & Francis. pp. 349-352.
- Axley, J. W. (2001). *Application of Natural Ventilation for US Commercial Buildings—Climate Suitability, Design Strategies & Methods, Modeling Studies*. Gaithersburg, MD, NIST.
- Balasbaneh A.T. & Marsono A. K. (2011). Hot & Humid Climate Air Flow Study and Affect of Stack Ventilation in Residential Building. *Proceeding of The International Conference on Environment and Industrial Innovation, IPCBEE vol.12*, IACSIT Press, Singapore
- Bauman, F. S., Ernest, D. R. & Arens, E. A. (1988). The Effects of Surrounding Building on Wind Pressure Distributions and Natural Ventilation in Long Building Row. *ASHRAE Transactions*, Vol. 94, Part 2, pp. 1670-1695. eScholarship Univ. of California.

- Behsh, B. (2002). Building Form As an Option for Enhancing The Indoor Thermal Conditions. Building Physics 2002-6th Nordic Symposium, pp. 759-766.
- Binggeli, C. (2003). Building systems for interior designers. John Wiley & Sons.
- Bodart, M. & Herde, A. (2002). Global energy saving in offices buildings by use of daylight. Energy and Buildings 34, pp 421-429. Elsevier Science Limited.
- Bojic, M., Yik, F. & Sat, P. (2001). Influence of thermal insulation position in building envelope on the space cooling of high-rise residential buildings in Hong Kong. Energy and Buildings, 33, 6, pp. 569-581. Elsevier Science Ltd.
- Bradley, J. S. & Gover, B. N. (2004). Criteria for Acoustic Comfort in Open-plan Offices. Proceeding of 33rd International Congress and Exposition on Noise Control Engineering, 22-25 August 2004, Prague, Rep. Czech, pp 1-6.
- Brunskill, R. W. (2000). Vernacular Architecture: An Illustrated Handbook. Faber and Faber.
- Building Regulatory Requirement (2010). Department of Housing and Public Work, Queensland.
- Busch, J. F. (1992). A tale of two populations: thermal comfort in air-conditioned and naturally ventilated offices in Thailand. Energy and buildings, 18(3), 235-249.
- Canas, I. & Martin, S. (2004). Recovery of Spanish vernacular construction as a model of bioclimatic architecture. Building and Environment, Vol. 39, pp 1477 -1495. Science Direct.
- Candido, C., de Dear, R., Lamberts, R. & Bittencourt, L. (2008). Natural Ventilation and Thermal Comfort: Air Movement Acceptability Inside Naturally Vntilated Building in Brazilian Hot Humid Zone. Proceeding of Conference: Air Conditioning and The Low Carbon Cooling Challenge, Cumberland Lodge, Windsor, U.K., 27-28 July 2008.
- Cheshire, P., & Magrini, S. (2009). Urban growth drivers in a Europe of sticky people and implicit boundaries. Journal of Economic Geography, 9(1), 85-115.

- Cheung, C. K., Fuller, R. J. & Luther, M. B. (2005). Energy Efficient Envelope Design for High Rise Apartment. *Energy and Building* 37, Issue 1, pp. 37 - 48. Elsevier Science Ltd.
- Chung, L. P. Ahmad, M. H., Ossen, D. R. & Hamid, M. (2015). Effective Solar Chimney Cross Section Ventilation Performance in Malaysian Terraced House.
- Clancy, E. (2011). Indoor Air Quality and Ventilation. CIBSE Knowledge Series: KS17. pp. 16-33.
- Clark, P. (2000). Ken Yeang. *Building.co.uk*, Issue 23. Retrieved <http://www.building.co.uk/ken-yeang/4327.article>
- Creswell, J.W. (2013). *Research Design: Qualitative, Quantitative and Mixed Method Approaches*. Sage Publication. California U.S.
- Daghigh, R. (2009). Thermal Comfort in Naturally Ventilated Office under Varied Opening Arrangements: Objective and Subjective Approach. *European Journal of Scientific Research* ISSN 1450-216X vol.26 No.2 (2009), pp 260-276.
- Darus, F. M., Zain-Ahmed, A., & Latif, M. T. (2011). Terraced residential housing indoor and outdoor air quality in Shah Alam, Malaysia. In *Sustainable Energy & Environment (ISESEE)*, 2011 3rd International Symposium & Exhibition in (pp. 204-208). IEEE.
- Davis, M. P., Nordin, N. A., Ghazali, M., Durak, M. J. & Reimann, G. (2005). Reducing Urban Heat Island Effect with Thermal Comfort Housing and Honeycomb Township. *Conference on Sustainable Building South East Asia*, 11-13 April 2005, Malaysia
- de Dear, R. J. & Brager, G. S. (1998). Developing an Adaptive Model of Thermal Comfort and Preference. *ASHRAE Transaction*. Vol. 104, Part 1. American Society of Heating, Refrigerating and Air Conditioning Engineers Inc., January 1998. pp 1-18
- de la Flor, F. S. & Dominguez, S. A. (2004). Modelling Microclimate in Urban Environments and Assessing Its Influence on the Performance of Surrounding Buildings. *Energy and Building* 36, pp. 403-413. Elsevier Science Ltd.

Eakes, J. (1999). What is neutral plane? Retrieved on 18 January 2015.
<http://joneakes.com/jons-fixit-database/723-WHAT-IS-THE-NEUTRAL-PLANE>

Elliott, L. (2002). Breaking Down Walls. *Old-House Journal*, pp. 50-53. Active Interest Media, Inc..

El-Shorbagy, A. M. (2010). Design With Nature: Wind Catcher As a Paradigm of Natural Ventilation Device in Buildings. *International Journal of Civil and Environmental Engineering*, Vol. 10, No. 3, pp. 26-31.

Etheridge, D. & Sandberg, M. (1996). *Building Ventilation: Theory and Measurement*. John Wiley & Sons, New York.

Evans, J. M. & Schiller, S. D. (1996). Application of Microclimate Studies in Town Planning: A New Capital City, An Existing Urban District and Urban River Front Development. *Atmospheric Environment* Vol.30, No.3, pp.361-364. Pergamon.

Fanger, P. O. (1970). *Thermal Comfort: Analysis and applications in environmental engineering*. Copenhagen s.n., pp. 244.

Fanger, P. O. (1972). *Thermal comfort: analysis and applications in environmental systems*. McGraw Hill, New York.

Fellaname (2010). Retrieved on 12 May 2017 from <http://upload.wikimedia.org/wikipedia/commons/5/58/Malqaf.jpg>.

Feriadi, H. & Wong, N. H. (2004). Thermal comfort for naturally ventilated houses in Indonesia. *Energy and Buildings*, 36(7), 614-626.

Flynn, I. E. & Spencer, T. J. (1977). The effects of light source colour on user impression and satisfaction, *Journal of the Illuminating Engineering Society*, April 1977. pp 167 -179.

Frizell, S. (2014). The New American Dream is Living in A City. Retrieved on 17 March 2017, from time.com/72281/american-housing/

Fuziah, R. (1990). *Heritage - The Changing World: Our Heritage and Our Future*. Dewan Bahasa dan Pustaka.

- Gan, G. (2010). Interaction Between Wind and Buoyancy Effects in Natural Ventilation of Buildings. *The Open Construction and Building Technology*, pp. 134-145. Bentham Open.
- Gao, C. F. & Lee, W., L. (2010) Evaluating the Influence of Openings Configuration on Natural ventilation Performance of Residential Units in Hong Kong. *Building and environment* 46 (2011) Elsevier Ltd. Pp.
- Ghiabaklou, Z., (2010). Natural Ventilation as a Design Strategy for Energy Saving. *World Academy of Science, Engineering and Technology*, 71. pp. 315-319.
- Ghiaus, C., & Allard, F. (2012). Natural ventilation in the urban environment: assessment and design. Earthscan.
- Givoni, B. (1976). Climate and architecture. Applied Science, London (1976). R. H. B. Excel], *Renewable Energy Rev. J.*, 1.
- Givoni, B. (1998). Climate Considerations in Building and Urban Design. John Wiley & Sons. pp. 5-8.
- Gong, N., Tham, K. W., Melikov, A. K., Wyon, D. P., Sekhar, S. C., & Cheong, K. W. (2006). The acceptable air velocity range for local air movement in the tropics. *Hvac&r Research*, 12(4), 1065-1076.
- Goodish, T. (2000). *Indoor Environmental Quality*. Lewis, USA.
- Green Building Index (2009). GBI Organization. Retrieved on 8 January 2014, from <http://new.greenbuildingindex.org/organisation/gbi>.
- Guzowski, M., (2010). *Towards Zero Energy Architecture*. Laurence King Publishing Ltd., London.
- Haase, M. & Amato, A. (2009). An Investigation of The Potential for Natural Ventilation and Building Orientation to Achieve Thermal Comfort in Warm and Humid Climate. *Solar Energy*, Vol. 83, Issue 3, pp. 389-399. Elsevier Science Ltd.
- Hanafi, Z. (1994). Housing design in relation to environmental comfort — a comparison of the traditional Malay house and modern housing. *Building Research and Information*, Vol. 22, Issue 1, pp. 21-33. Taylor & Francis.

- Hassan, A. S. & Ramli, M. (2010). Natural Ventilation of Indoor Air Temperature: A Case Study of The Traditional Malay House in Penang. *American Journal of Engineering and Applied Sciences*, Vol. 3, No. 3, pp. 521-528.
- Heiselberg, P., Svidt, K., & Nielsen, P. V. (2001). Characteristics of airflow from open windows. *Building and Environment*, 36(7), 859-869.
- Hidayat, W. (2011). Application of Malay Traditional Architecture Elements as Regional Identity towards Sustainable Architecture. *Jurnal Ruas*, Vol. 9, No. 2. Universitas Brawijaya.
- Holden, E., & Norland, I. T. (2005). Three challenges for the compact city as a sustainable urban form: household consumption of energy and transport in eight residential areas in the greater Oslo region. *Urban studies*, 42(12), 2145-2166.
- Holmes, M. J. & Hacker, J. (2007). Climate Change, Thermal Comfort and Energy: Meeting the Design Challenges of the 21st Century. *Energy and Buildings* 39, pp. 802-814. Elsevier Science Ltd.
- Huat, N. B. & Akasah, Z. A. (2011). An Overview of Malaysia Green Technology Corporation Office Building: A Showcase Energy-Efficient Building Project in Malaysia. *Journal of Sustainable Development*, Vol. 4, No. 5, pp. 212-228. Canadian Centre of Science and Education.
- Hughes, B. R. & Ghani, A. A. A. (2010). A Numerical Investigation into The Effect of Windvent Louvre External Angle on Passive Stack Ventilation Performance. *Building and Environment*, Vol. 45, Issue 4, pp. 1025-1036. Elsevier Science Ltd.
- Huo, Y. (1997). Ventilation Impact on Indoor Air Quality Problems in Partitioned Office. PhD Thesis, Concordia University Montreal, Quebec, Canada.
- Ing, T. P., Seng, L. K., Jerry, S. P. M. & Teng, C. S. (2010). Handbook for PAM Contract. Pertubuhan Akitek Malaysia, Kuala Lumpur.
- Instrumentchoice. (2013). Retrieved on 19 May 2017 from <http://www.instrumentchoice.com.au/instrument-choice>

Ismail M. R. (2000). An Investigation into the Choice of Air-Conditioning Design Conditions for Malaysian Offices and Their Effect on Energy Consumption in Malaysia. PhD Thesis, University of Liverpool, UK.

Ismail, L. H., Sibley, M., & Wahab, I. A. (2011). Bioclimatic technology in high rise office building design: a comparison study for indoor environmental condition. *Journal of Science and Technology*, 3(2).

Ismail, L. H. (2007). An Evaluation of Bioclimatic High Rise Office Building in A Tropical Climate: Energy Consumption and Users' Satisfaction in Selected Office Buildings in Malaysia. PhD Thesis, University of Liverpool, UK.

Ismail, M. R., & Barber, J. M. (2001). A field study to determine inside design conditions for Malaysian air conditioning systems. *Architectural Science Review*, 44(1), 83-99.

Ismail, M. & Rahman, A. M. A. (2012). Stack Ventilation Strategies in Architectural Context: A Brief Review of Historical Development, Current Trends and Future Possibilities. *International Journal of Recent Research of Applied Study*, Vo. 11, No.2, pp. 291-301.

Jamaluddin N., Mohammed, N.I., Khamidi, M. F. & Wahab, S. N. A. (2015). Thermal Comfort of Residential Building in Malaysia in Different Micro Climates. *Procedia - Social and Behavioral Sciences* (Vol. 170) pp. 613-623, Elsevier Science Limited.

Jamaludin, A. A., Hussein, H., Ariffin, A. R. M. & Keumala, N. (2014). A Study on Different Natural Ventilation Approach at a Residential College Building with the Internal Courtyard Arrangement. *Energy and Building* 72, pp. 340 -352. Elsevier Science Ltd.

James, P. A. B., Jentsch, M. F., Bahaj, A. S., & Uittenbogaard, J. G. M. (2005). Assessment of Building Envelope Refurbishment Options to Achieve Sustainable Energetic Performance in a High Thermal Mass Office Building, *Proceeding of Conference on Sustainable Building South East asia*, 11-13 April 2005, Malaysia, pp 522 – 529.

- Jiang, Y., Alexander, D., Jenkins, H., Arthur, R. & Chen, Q. (2003). Natural ventilation in buildings: measurement in a wind tunnel and numerical simulation with large eddy simulation. *Journal of Wind Engineering and Industrial Aerodynamics*, 91(3), pp. 331-353. Elsevier Science Ltd.
- Johansson, E., (2006). Influence of urban geometry on outdoor thermal comfort in a hot dry climate: A study in Fez, Morocco. *Energy and Building* 41, pp. 1326-1338. Elsevier Science Ltd.
- Kato, S., Murakami, S., Mochida, A., Akayabashi, S. & Tominaga, Y. (1992). Velocity Pressure Field of Cross Ventilation With Open Windows Analyzed By Wind Tunnel and Numerical Simulation. *Journal of Wind Engineering and Industrial Aerodynamic* 41-22, pp. 2575-2586. Elsevier Science Ltd.
- Khoukhi, M., & Al-Maqbali, A. (2011). Stack pressure and airflow movement in high and medium rise buildings. *Energy Procedia*, 6, 422-431.
- Kleiven, T. (2003). Natural ventilation in buildings: architectural concepts, consequences and possibilities. Institutt for byggekunst, historie og teknologi.
- Kontoleon, K. J. (2013). Energy Saving Assessment in Buildings with Varying Façade Orientations and Types of Glazing Systems when Exposed to Sun. *International Journal of Performability Engineering* Vol. 9, No. 1, pp. 33-48. RAMS Consultants.
- Kotani, H., & Yamanaka, T. (2008). Interference coefficient for discharge coefficient in prediction of cross ventilation rate through large opening. In *Proceedings of 29th AIVC Conference* (Vol. 3, p. 27e33).
- Krausse, B., Cook, M. J. & Lomas, K. J. (2006). Environmental Performance of Anaturally Ventilated City Centre Library. *Proceeding of the International Conference on Comfort and Energy Use in Building*, Windsor, U.K., 27-30 April 2006.
- Kubota, T. & Ahmad, S. (2006). Wind Environment Evaluation of Neighborhood Areas in Major Towns of Malaysia. *Journal of Asia Architecture and Building Engineering*, Vol. 5, No. 1, May 2006, pp. 1-8.

- Kubota, T., Miurab, M., Tominagac, Y. & Mochidad, A. (2008). Wind tunnel tests on the relationship between building density and pedestrian-level wind velocity: Development of guidelines for realizing acceptable wind environment in residential neighborhoods. *Building and Environment* 43, pp. 1699–1708. Elsevier Science Ltd.
- Kwok, A., & Grondzik, W. (1999). The Logan House: Measuring Air Movement. In *Proceeding of the Solar Conference* (pp. 635-640). American Solar Energy Society; American Institute of Architect.
- Kwok, A. G. & Grondzik, W. T. (2007). The Green Studio Handbook: Environmental Strategies for Schematic Design. *ARCC Journal for Architectural Research*, Vol. 4, Issue 2, pp. 43-50. ENQ.
- Kwong, Q. J., Adam, N. M., & Sahari, B. B. (2014). Thermal comfort assessment and potential for energy efficiency enhancement in modern tropical buildings: A review. *Energy and Buildings*, 68, 547-557.
- Larsen, T. S., Heiselberg, P. (2008). Single Sided Natural Ventilation Driven by Wind Pressure and Temperature Difference. *Energy and Building*, Vol. 40, Issue 6, pp. 1031-1040. Elsevier Science Ltd.
- Leaman, A., & Bordass, B. (2007). Are users more tolerant of 'green' buildings?. *Building Research & Information*, 35(6), 662-673.
- Li, R., Pitts, A. C., & Li, Y. (2007). Buoyancy-driven natural ventilation of a room with large openings. In *The proceedings of building simulation 2007*, 10th conference of the international-building-performance-simulation-association Tsinghua University, Beijing (pp. 984-991).
- Li, Y. Y., Zhang, H., & Kainz, W. (2012). Monitoring patterns of urban heat islands of the fast-growing Shanghai metropolis, China: Using time-series of Landsat TM/ETM+ data. *International Journal of Applied Earth Observation and Geoinformation*, 19, 127-138.
- Liddament, M. W. (1996). A guide to energy efficient ventilation, Air Infiltration and Ventilation Center, Coventry, UK.

- Liddament, M. W. (2000). A Review of Ventilation and the Quality of Ventilation Air. International Journal of Indoor Environment and Health (INDOOR AIR) Vol. 10, Issue 3, pp. 193 - 199. Wiley UK.
- Lim, J. Y. (1987). The Traditional Malay House: Indigenous and traditional knowledge and practices. pp.73-81.
- Liping, W. & Hien, W. N. (2007). The Impacts of Ventilation Strategies and Facade on Indoor Thermal Environment for Naturally Ventilated Residential Buildings in Singapore. Building and Environment 42, pp. 4006–4015. Elsevier Science Ltd.
- Lomas, K. (2007). Architectural design of an advanced naturally ventilated building form. Energy and Buildings 39, pp. 166–181. Elsevier Science Ltd.
- Lombard, L. P., Ortiz, J. & Pout, C. (2008). A Review on Building Energy Consumption Information. Energy and Building 40 (2008), pp 394-398. Elsevier Science Limited.
- Luo, Q., Liu, Z., & Tang, G. (2007). Influence analysis of neutral plane on ventilation in workshop. In Proceedings of Building Simulation.
- Malaysia (1984). Uniform Building By-Law.
- Malaysian Standard 1525:2014. Energy efficiency and use of renewable energy for non-residential buildings - Code of practice. (Department of Standards Malaysia) (2014)
- Mallick, F. H. (1996). Thermal comfort and building design in the tropical climates. Energy and Buildings 23 (1996), pp 161-167. Elsevier Science Limited.
- McHarg, I. L. (1992). Design With Nature. John Wiley & Sons Inc., N.York, USA.
- Md. Tap, M., Kamar, H. M., Kamsah, A. K. M. N., & Salimin, K. A. M. (2011). Simulation of thermal comfort of a residential house. *IJCSI*. Montazeri, H., Azizian, R. (2008). Experimental Study on Natural Ventilation Performance of One Sided Wind Catcher. Building and Environment. Elsevier Science Ltd.
- Morbitzer, C., Stratchan, P., Webster, J., Spires, B. & Cafferty, D. (2001). Integration of Building Simulation Into the Design Process of An Architectural Practice.

Proceeding of Seventh IBPSA Conference, 13-15 August 2001, Rio de Janeiro, pp. 697-704.

Najafian, M., Bahrami, A. B. (2012). The Effect of Orientation on Optimum Insulation Position in the Wall of a Building with Natural Ventilation in Hot and Dry Climate. *International Journal of Advanced Design and Manufacturing Technology*, Vol. 5, No.3, pp. 93-98. IAU Majlesi.

Nakanishi, T. (2007). Investigation of Air Flow Passing Through Louvers. *Komatsu Technical Report* Vol. 53, No. 160.

Nasir, A. H. & Hashim, W. (2011). *The Traditional Malay House*. Institut Terjemahan Negara Malaysia Berhad.

Ng, E., Chen, L., Wang, Y., & Yuan, C. (2012). A study on the cooling effects of greening in a high-density city: an experience from Hong Kong. *Building and Environment*, 47, 256-271.

Ngom, L. T. (2012). A Language of Architecture. *Architecture Asia*, Issue 3 July/Aug./Sept 2012. Pusat Binaan SB, Kuala Lumpur.

Nguyen, A. T., Tran, Q. B., Tran, D. Q., & Reiter, S. (2011). An investigation on climate responsive design strategies of vernacular housing in Vietnam. *Building and Environment*, 46(10), 2088-2106.

Nicol, J. (2004). Adaptive thermal comfort standards in the hot-humid tropics. *Energy and Buildings* 36 (2004), pp 628–637. Elsevier Science Limited.

Nieuwolt, S. (1977). *Tropical Climatology: An Introduction to the Climate of the Low Latitudes*. John Wiley and Sons, London.

Nikolopoulou, M., Baker, N. & Steemers, K. (2001). Thermal Comfort in Outdoor Urban Spaces: Understanding the Human Parameter. *Solar Energy* Vol. 70, No. 3, pp. 227–235, Pergamon.

Noh, M. H. M., Rashid, H., Hamid, A. H. A. & Iskandar, M. F. (2010). Comparison of Numerical Investigation on Airfoil and Flat Louvers on The Air Duct Intake. *Procedia Engineering* 41, pp. 1761-1768. Elsevier Science Ltd.

Oke, T. R. (1973). City size and the urban heat island. *Atmospheric Environment* (1967), 7(8), 769-779.

Olgyay, V. (1963). *Design with Climate*. Princeton University Press, Princeton: New Jersey.

Olufowobi, M. B., & Adenuga, O. A. (2012). Towards the specification of windows sizes for natural ventilation in classrooms in a warm climate, Nigeria. *Journal of Building Performance*, 3(1).

Ooi, J. B. (1963). *Land, people and economy in Malaya*.

Osborn, D., & Greeno, R. (2006). *Introduction to building*. Pearson Education.

Parasonis, J., Keizikas, A. & Kalibatiene, D. (2012). The Relationship between the Shape of A Building and Its Energy Performance. *Architectural Engineering and Design Management* 8:4, pp246-256. Taylor & Francis

Peel, M. C., Finlayson, B. L. & MacMahon, T. A. (2011). Koppen World Map Hi-Res.png. Retrieved on 12 March 2016, from https://commons.wikimedia.org/wiki/File:Koppen_World_Map_Af_Am_Aw.png

Rahman, S. A., & Kannan, K. S. (1997). Air flow and thermal simulation studies of wind ventilated classrooms in Malaysia. Special issue world renewable energy congress, energy efficiency and the environment. *Renewable Energy*, 8(1-4), 264-266.

Rajapaksha, I., Nagai, H., & Okumiya, M. (2003). A ventilated courtyard as a passive cooling strategy in the warm humid tropics. *Renewable Energy*, 28(11), 1755-1778.

Rameli, A., Johar, F. & Ho, C. S. (2006). The Management of Housing Supply in Malaysia: Incorporating Market Mechanisms in Housing Planning Process. In *Proceeding of International Conference on Construction Industry 2006 (ICCI 2006)*, 22-23 June 2006, Padang, Sumatera, Indonesia.

Razorblade Pairs (2012). *Architecture Malaysia*, Vol. 24, p. 58-63. Pertubuhan Akitek Malaysia, Kuala Lumpur.

- Rizk, A. A., Al-Samadony, Y.A., A-kunbr, U. & Elwan, M.M. (2015). An Improved Cross Ventilation Model in Windy Region. European Scientific Journal. Special Edition, Vol. 1, pp. 621 - 641, ESI. Macedonia.
- Rizwan, A. M., Dennis, L. Y., & Chunho, L. I. U. (2008). A review on the generation, determination and mitigation of Urban Heat Island. Journal of Environmental Sciences, 20(1), 120-128.
- Roche, P. L. & Milne, M. (2004). Effects of Window Size and Thermal Mass on Building Comfort Using an Intelligent Ventilation Controller. Solar Energy, Vol. 7, pp. 421-434. Elsevier Science Ltd.
- Roof-Roof House (2006). Retrieved on 14 August 2015 from <http://archnet.org/sites/800>.
- Sabarinah, S. A. (2002). A Review on Interior Comfort Conditions in Malaysia. ANZAScA Conference 2002. The University of Queensland, Brisbane, Australia.
- Samirah, A. R. & Kannan, K. S. (1996). Air Flow and Thermal Simulation Studies of Wind Ventilated Classroom in Malaysia. Special issue World Renewable Energy, Vol. 8, Issue 1-4, pp 264-269.
- Santamouris, M., Pavlou, C., Syneffa, A., & Niachou, K. (2006). Recent progress on passive cooling techniques. Advanced technological developments to improve indoor environmental quality in low income households. In PREA workshop.
- Sapian, A. R., Madros, N. H., & Ahmad, M. H. (2001). Evaluation of thermal comfort performance in low cost flats: case study of Sri Perak flats, Kuala Lumpur. Development of passive solar design and technology in tropical climates.
- Schmidt, D., Maas, A., & Hauser, G. (1999). Experimental and theoretical case study on cross ventilation: Designing a mathematical model. Nordic J. Build. Phys, 2, 1-17.
- Schiavon, S., Yang, B., Donner, Y., Chang, V. C., & Nazaroff, W. W. (2017). Thermal comfort, perceived air quality, and cognitive performance when personally

controlled air movement is used by tropically acclimatized persons. Indoor air, 27(3), 690-702.

Sekeping Serendah (2012). Retrieved on 14 August 2015 from <http://www.sekeping.com/serendah/home.html>.

Siew, C. C., Che-Ani, A. I., Tawil, N. M., Abdullah. N. A. G. & Mohd-Tahir, M. (2011). Classification of Natural Ventilation Strategies in Optimizing Energy Consumption in Malaysian Office Building. *Procedia Engineering* (20), pp. 363-371. Elsevier Science Ltd.

Sivakumar, S. (2012). Building Envelope Wind Pressure Manipulation for Application in Streamlined High-Rise Buildings. *Mechanical and Aerospace Engineering - Dissertations*. Paper 75.

Sonnenwald, D. H. (1996). Communication Roles That Support Collaboration During the Design Process. *Design Studies* 17, pp. 277-301. Elsevier Science Ltd.

Stein, B. & Reynolds, J. S. (2000). *Mechanical and Electrical Equipment for Building* (9th Edition). John Wiley & Sons, New York.

Straube, J. (2007). *Air Flow Control in Building*. Building Science Corporation. Retrieved on 6 Desember 2015 from <https://buildingscience.com/documents/digests/bsd-014-air-flow-control-in-buildings>

Tamura, T., Nozawa, T. & Konji, K. (2006). AIJ guide for numerical prediction of wind loads on buildings. *Proceeding of The 5th International Symposium on Computational Wind Engineering*, Yokohama, Japan.

Tantasavasdi, C., Srebric, J. & Chen, Q. (2001). Natural Ventilation Design for Houses in Thailand. *Energy and Building* 33(8), pp 815-824. Elsevier Science Ltd.

Thorsson, S., Honjo, T., Lindberg, F., Eliasson, I. & Lim, E.M. (2007). Thermal Comfort and Outdoor Activity in Japanese Urban Public Places. *Environment and Behavior* 2007:39, pp. 660-684. Sage Publication.

Thuraisingham, T. D. (2013). The Architect as Contract Administrator: Dilemma Over Time Extension. *Pertubuhan Akitek Malaysia CPD Seminar*, 8 June 2013, Kuala Lumpur.

- Tominagaa, Y., Mochidab, A., Yoshiec, R., Kataokad, H., Nozue, T., Yoshikawaf, M. & Shirasawac, T. (2008). AIJ guidelines for practical applications of CFD to pedestrian wind environment around buildings. *Journal of Wind Engineering and Industrial Aerodynamics* 96, pp. 1749–1761. Elsevier Science Ltd.
- Tyler, J. M., Hinton, L. V. & Olin, J. G. (2012). State Standards, Regulations, and Responsibilities in Noise Pollution Control, *Journal of Air Pollution Control Association*. 24-2 (2012), pp 130-135. Taylor & Francis. USA.
- Verma, S. K., Ahuja, A. K. & Pandey, A. D. (2013). Effects of Wind Incidence Angle on Wind Pressure Distribution on Square Plan Tall Buildings. *Journal of Academic Industrial Research* Vol.1(12), pp. 747-752. Youth Education and Research Trust (YERT).
- Veronica, N. (2015). House: Chempenai. *Architecture Malaysia*, Vol. 27, Issue 1 February 2015, pp. 27-31. Pertubuhan Akitek Malaysia, Kuala Lumpur.
- Visagavel, K. & Srinivasan, P.S. (2009). Analysis of Single Side Ventilated and Cross Ventilated Rooms by Varying the Width of the Window Opening Using CFD. *Solar Energy*, Vol. 83, Issue 1, pp. 2-5. Elsevier Science Ltd.
- Wahab, I.A. & Ismail, L.H., (2012). Undang-Undang Pembinaan Untuk Pembangunan Perumahan. pp. 40 - 43. Penerbit UTHM, Batu Pahat, Johor.
- Walikewitz, N., Jänicke, B., Langner, M., Meier, F., & Endlicher, W. (2015). The difference between the mean radiant temperature and the air temperature within indoor environments: A case study during summer conditions. *Building and Environment*, 84, 151-161.
- White, E. T. (1983). *Site Analysis: Diagramming Information for Architectural Design*, Architectural Media Ltd, 1983.
- Wolkoff, P., & Kjærgaard, S. K. (2007). The dichotomy of relative humidity on indoor air quality. *Environment International*, 33(6), 850-857.
- Wong, N. H., Han, M., Cheng, V., Chan, T. Y. & Wong, K. S. (2005). Towards Better Wind, Daylight and Natural Ventilation for Buildings and Urban Spaces in Ultra Dense Cities - An Experience from Hong Kong. *Proceeding of*

Conference on The 2005 World Sustainable Building Conference, 27-29 September 2005, Tokyo, pp 2087-2094.

Yau, Y. H., Ding, L. C. & Chew, B. T. (2011). Thermal Comfort and Indoor Air Quality at Green Building in Malaysia. United Kingdom-Malaysia-Ireland Engineering Science Conference 2011 (UMIES 2011), Kuala Lumpur.

Yeang, K. (1997). Designing the green skyscraper. In Conquest of vertical space in the 21st century. International conference (pp. 13-27).

Yin, R. K. (2015). Qualitative research from start to finish. Guilford Publications, pp. 3-6.

Zain, Z. M., Taib, M. N., & Baki, S. M. S. (2007). Hot and humid climate: prospect for thermal comfort in residential building. Desalination, 209(1-3), 261-268.

Zhang, J. Y., Lu, W. Z., Huo, R., & Feng, R. (2008). A new model for determining neutral-plane position in shaft space of a building under fire situation. Building and environment, 43(6), 1101-1108.

Zhang, Y., Lin, K., Zhang, Q., Di, H. (2006). Ideal Thermophysical Properties for Free-cooling (or Heating) Buildings with Constant Thermal Physical Property Material. Energy and Building, 38, pp. 1164-1170. Elsevier Science Ltd.



PT TAA
PERPUSTAKAAN TEKNIK DAN ARSITEKTUR